

RADAR MANAGEMENT SYSTEM



NETWORKED I/O Specifications	NIO-DINM	NIO-DINS	NIO-VM	HOSTED NIO
DIMENSIONS	7.5 X 9 X 3 in 192 x 230 x 77 mm	6.64 x 5.19 x 1.90 in 168 x 132 x 48 mm	N/A	N/A
WEIGHT	6.8 lbs 3.08 Kg	2.9 lbs 1.3 Kg	N/A	N/A
NUMBER OF DEVICES SUPPORTED	10, 25 or 50	10 or 25	10, 25 or 50	10, 25 or 50
NUMBER OF ZONES	200	200	Up to 200	Up to 200
I/O OUTPUT ADD-ON	YES	YES	YES	YES
SYSTEM POWER REQUIREMENTS	9-36 VDC (32W Typical, 116W Max)	18-36 VDC (12W Typical, 25W Max)	N/A	N/A
OPERATIONAL TEMPERATURE RANGE	-10°C to 50°C -14° F to 122° F	-40° C to 60° C -40° F to 140° F	N/A	N/A
OUTPUT FORMAT	JSON, Web UI, Onvif, XML	JSON, Web UI, Onvif, XML	JSON, Web UI, Onvif, XML	JSON, Web UI, Onvif, XML
RTSP / AI	Yes	Yes	Yes	Yes
HARDWARE	Advantech MIC-770 INTEL I5 8500 RAM: 16 GB HD: 128 GB SSD	SeaLevel Relio R1 INTEL I5 7300U RAM: 16GB HD: 128GB SSD	N/A	N/A
CERTIFICATIONS	CE, FCC Class A, CCC, BSMI, CB/UL	FCC, RoHS, REACH	N/A	N/A

