



SPOTTER

MOBILE SURVEILLANCE KIT
(MSK™)



A Full Anti-Drone Suite - On a Tripod

Everything you need for event/temporary site security in one compact, fully integrated system.

Easy to **move**, easy to **power**, easy to **operate**

PTZ Camera

Mount any PTZ Camera on the top of the MSK System and the system will autocue its lens to detected targets

REMOTE DRONE ID (RDID™)

Track drones **and** drone pilots over a wide area, 3km radius (700+ acres), with zero false alarms

LIVE STREAM

Live stream the MSK's surveillance data from anywhere in the world via a local network connection or Starlink satellite

SPOTTER RADARS

Choose any Spotter Global radars to provide wide-area ground surveillance (100 m-1500 m detecting walkers)

FIRST TO DETECT. FIRST TO PROTECT.™

FOR MORE INFORMATION CONTACT:

sales@spotterglobal.com

801-742-5849

www.spotterglobal.com

MSK Features

- Compatible with C, CK, GK, GX, and AX Series Radars from Spotter Global
- Tripod/Mounting Hardware/Cables
- NetworkedIO (NIO) C2
- Custom built with the sensor suite you need
- Five Sensor Mounting Points(1 Top, 4 Sides)
- License Points for 2 radars, 1 RDID, and 1 Camera
- Purchase or lease options available
- NOTE: Camera not included. MSK is compatible with most camera manufacturers

NetworkedIO (NIO) serves as the system’s centralized C2 engine, orchestrating autonomous slew-to-cue optical verification and ensuring full-spectrum interoperability between onboard sensors and external third-party platforms.

MSK Specifications

Dimensions	10.75 X 10.75 X 10.33 IN	GPU	NVIDIA® Ampere 2048 CUDA® cores 930 MHz Max MADE IN USA
Temperature Ranges	-25 C to 65 C	CPU	8-core Arm® Cortex®-A78AE CPU
Input Voltage	24V-36V	RAM	16GB 256-bit LPDDR5
Power Consumption	Min: 15 Watts Max: 325 Watts	Long-term Memory	256GB NVMe
Base Weight	33 lbs	Output Format	JSON, Web UI, Onvif, XML
*Total weight varies based on sensors and camera used.		Certifications	FCC, CE, RoHS, REACH

